PRODUCT SPECIFICATION SHEET



PRODUCT: ClearitWell™

MANUFACTURER: Blue Earth Products® 14580 West 99th Street, Lenexa, KS 66215 Phone: 1.800.259.4472

BENEFITS: ClearitWell improves flow rates and water quality in water wells resulting from biofouling and associated deposit accumulations. Periodic treatments provide continuous maximum well performance. ClearitWell treatments are less

corrosive to metals (safer on pumps, casings, and screens) and more effective at breaking down biofouling (underlining source of most deposit buildups) than other traditional chemical treatments. ClearitWell also works well as a cleaning

aid during mechanical well remediations.

DESCRIPTION: ClearitWell is an NSF certified well cleaning and rehabilitation aid. It is a two part product which includes, as an

ingredient, the deposit removing power of Blue Earth Products' Clearitas® product. ClearitWell aggressively breaks

 $down\ the\ deposits\ and\ fouling\ that\ block\ water\ flow\ through\ screens,\ gravel\ pack,\ and\ aquifers.$

PROPERTIES: Part A Part B

Composition Clearitas / Sodium Hypochlorite Blend Organic Acid
Weight 9.0 lbs. per gallon 8.7 lbs. per gallon

ColorYellowClearOdorChlorineOdorless

pH 12

APPLICATION: ClearitWell is used by mixing each part with water then pouring the treated water into the well. A single 10 gal batch

of ClearitWell (5 gal of each component) makes 330 gallons of treatment solution. A ClearitWell treatment requires treatment solution equal to 2 to 5 times the borehole volume. (ex. 10 gal of ClearitWell will treat a borehole size of 64 to 160 gal) After dosing, let the well soak for 24 to 72 hours and then flush to waste. Detailed instructions are provided

with the product.

STORAGE: Store ClearitWell locked up in original container or corrosive resistant container and avoid exposure to direct sunlight

and heat.

DISPOSAL: ClearitWell should be disposed of according to local, state and federal regulations.

SAFETY: ClearitWell causes severe skin burns and eye damage, is toxic to aquatic life, may be corrosive to metals and must be

handled according to the Safety Data Sheet. Use immediately after mixing Part A and Part B into the treatment solution,

insuring good ventilation, the mixture has potential for chlorine gas evolution.



NSF/ANSI: Standard 60 Certified – Well Cleaning Aid, Well Rehabilitation Aid

WARNING: Handle all Blue Earth Products' ClearitWell products according to Safety Data Sheets. Use immediately after mixing Part

A and Part B into the treatment solution, insuring good ventilation, the mixture has potential for chlorine gas evolution.

Visit us on the Web: <u>www.BlueEarthProducts.com</u>

The information set forth herein is furnished free of charge and is based on technical data that Blue Earth Products LLC believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents. CLEARITAS IS A REGISTERED TRADEMARK OF BLUE EARTH LABS LLC. (REV:01)

